

6 Channel Rotating Amplifier Module

Model LWEH-6L

- Mounts directly to LW Series Wheel Load Transducer
- Provides pilot and connector for SR/ERT series slip ring
- Precision low noise differential amplifiers
- Stable bridge excitation
- High level voltage signal output
- Remote bridge excitation On/Off capability
- Remote shunt calibration capability
- Not affected by temperature rise due to braking
- Environmentally sealed



Description

The *6 Channel Rotating Amplifier Module* is designed to mount directly to the Wheel Load Transducer. Michigan Scientific SR/ERT series slip ring with resolver mounts directly to the amplifier module. Superior data accuracy is achieved by locating the signal amplifiers on the rotating side of the slip ring. Errors due to lead wires length, connector resistance variations, and electro-magnetic interference are greatly reduced with the rotating amplifier module.

This *6 Channel Rotating Amplifier Module* incorporates precision low drift bridge excitation, stable differential amplifiers, and remotely activated shunt calibration resistors for system span verification. When mounted to the wheel load transducer, the amplifier module provides strain gage bridge excitation and amplification for six channels. The amplifier module is rugged enough to withstand pot hole and curb bumping impacts. Thermal stability is excellent, making it suitable for brake development work including repeated stops from highway speeds. All connections are made during assembly and sealed to withstand wet road conditions.

8500 Ance Road
Charlevoix, MI 49720
Tel: 231-547-5511
Fax: 231-547-7070

MICHIGAN SCIENTIFIC
<http://www.michsci.com>
Email: mcsinfo@michsci.com
corporation

321 East Huron Street
Milford, MI 48381
Tel: 248-685-3939
Fax: 248-685-5406

Rev: 7/25/11

6 Channel Rotating Amplifier Module

Specifications

PARAMETER	SPECIFICATION
BRIDGE EXCITATION	
Type	DC Constant Voltage (Bipolar excitation)
Magnitude	10 Volts
Accuracy	0.40%
Temperature Coefficient	0.0005%/°C Max (0.00028 %/°F)
Current Limit	84 mA/channel
REMOTE CALIBRATION	
	Positive & negative shunt calibration
Shunt Resistance	Matched to Wheel Load Transducer Range
Shunt Accuracy	0.50%
GAIN	
	Matched to Wheel Load Transducer Range
Range	w/ jumper w/ external resistor
	100 & 2000 V/V 100 through 2000 V/V
Accuracy	@ 25°C, Gain =100 @ 25°C, Gain =1000
	±0.05 %typ (±0.50 % max) ±0.50 %typ (±1.0 %max)
Temperature Coefficient	0.0025 %/°C (0.0014 %/°F)
OUTPUT	
Range	±10V Max
Capacitive Load	1000 pF Max
VOLTAGE OFFSET	
	Referred to input of amplifier
Initial	@ 25°C
	±10 µV
Temperature Stability	±0.1 µV /°C
Time Stability	±1.0 µV / Month
DC CMRR	160 dB
Noise	rti 0.01 to 10 Hz
	0.7 µV p-p
DYNAMIC RESPONSE	
Frequency Response	@ Gain=1000 -3dB @ Gain=100
	1 kHz 10 kHz
Slew rate	0.5 V/ µs
Settling Time to 0.01%	@ Gain=100
	145 µs
POWER REQUIREMENTS	
Voltage	@ 25°C
	±13 to ±17 VDC
Current	±100 mA plus Bridge Load (+100 mA additional during shunt calibration)
ENVIRONMENT	
Specification	-25 to +85°C (-13 to +185°F)
Operation	-55 to +125°C (-67 to +257°F)
MECHANICAL	
Weight	1.2 kg (2.5 lbs)

8500 Ance Road
Charlevoix, MI 49720
Tel: 231-547-5511
Fax: 231-547-7070
Rev: 7/25/11

MICHIGAN SCIENTIFIC
corporation

<http://www.michsci.com>
Email: mscinfo@michsci.com

321 East Huron Street
Milford, MI 48381
Tel: 248-685-3939
Fax: 248-685-5406