

Weatherproof Tubular Slip Ring Assembly

Model BA-T-1.2W

- Ideal for automotive half shaft
- Mounts on shafts up to 1.2" in diameter*
- Optional 60 pulse encoder
- Built-in strain gage amplifier
- Rugged stainless steel construction
- Permanently lubricated bearings
- Instrumentation quality rings and brushes
- High level signal output

*Larger diameter bores available, consult factory



Description

Michigan Scientific's *BA-T-1.2W Weatherproof Slip Ring Assembly* is ideal for applications that require a slip ring to be mounted directly on a rotating shaft. Designed to make long-term, all-weather (not submersible), torque measurements on automotive half shafts, the *BA-T-1.2W* can be used in other applications with shafts up to 1.2 inch diameter. A major feature of the *BA-T-1.2W* is its built-in strain gage amplifier located on the spinning side of the slip ring. This arrangement greatly improves the signal quality of the system by reducing errors due to long lead wires, connector resistance variations, and electro-magnetic interference.

Four of the seven slip ring circuits in the *BA-T-1.2W* are used to power and control the built-in model *AMP-SG1-M1* amplifier. Two additional ring circuits are used to transmit a high-level data signal. The seventh ring is for use with an optional configuration that utilizes two built-in amplifiers to provide two high-level data signals. Connections from the strain gage bridge to the amplifier are made via color-coded solder terminals located on the slip ring rotor. Each slip ring assembly includes a 15 ft stator cable with a protective rubber boot for the connector at the slip ring.

Specifications

Data Channel Options	<ul style="list-style-type: none">• 1 High Level Strain Gage Output• 2 High Level Strain Gage Outputs• 1 High Level Strain Gage Output and 2 Amplified Thermocouple Outputs
Temperature Range, slip ring	-40°F to 300°F (-40°C to 149°C)
Encoder operating temperature range	-40°F to 300°F (-40°C to 149°C)
Amplifier operating temperature range	-67°F to 257°F (-55°C to 125°C)
RPM Rating	3,500 rpm
Width	2.38 in (60.3 mm)
Diameter	3.29 in (83.5 mm)
Weight	2.3 lbs (1.0 kg)


8500 Ance Road
Charlevoix, MI 49720
Tel: 231-547-5511
Fax: 231-547-7070
04-6-20
Rev. A

MICHIGAN SCIENTIFIC
corporation
<http://www.michsci.com>
Email: msscinfo@michsci.com

321 East Huron Street
Milford, MI 48381
Tel: 248-685-3939
Fax: 248-685-5406

Weatherproof Tubular Slip Ring Assembly

BA-T-1.2W Configuration



NOTE: THE AMPLIFIER BUILT INTO THE ROTOR OF THE SLIP RING ASSEMBLY PROVIDES EXCITATION TO THE STRAIN GAGE BRIDGE

C566028A
BA-T-1.2W
02/01/2007

Encoder option

The encoder included in the *BA-T-1.2W/E60* tubular slip ring produces a 60 pulse/revolution 5-volt square wave. The TTL compatible signal is produced by a hall-effect sensor, which allows speed to be determined down to 0 rpm. The voltage required to drive the encoder can range from 5.5 to 45 DC volts.

Thermocouple amplifier option is available

8500 Ance Road
Charlevoix, MI 49720
Tel: 231-547-5511
Fax: 231-547-7070
04-6-20
Rev. A

MICHIGAN SCIENTIFIC
corporation
<http://www.michsci.com>
Email: mcsinfo@michsci.com

321 East Huron Street
Milford, MI 48381
Tel: 248-685-3939
Fax: 248-685-5406